



APPLICATION AND REPORT FORM FOR THE ATPL(A) SKILL TEST, TYPE RATING SKILL TEST AND PROFICIENCY CHECKS ON MULTI PILOT AEROPLANES AND SINGLE PILOT COMPLEX AEROPLANES WITH HIGH PERFORMANCE ACCORDING TO APPENDIX 9 TO COMMISSION REGULATION (EU) NO 1178/2011 OF 3 NOVEMBER 2011

A.	Skill test ATPL		B. to	be	Date of te	est	
			com	pleted by			
	Skill test type rating		exan	niner	Licence endorsement (type of aircraft)		
	Skill test Cruise relief co	o-pilot					
	Skill test CRCP remova	ıl					
	PC Revalidation		Multi pilot a	aeroplane	Test per	formed in;	
	PC Renewal		Single pilo	t aeroplane (SPO)	Aircraft		
	PC applicable for Cruise	e relief	Single pilo	t aeroplane (MPO)	)) FSTD(s)		
	co-pilot		If both SPO and are sought, com	l MPO privileges plete TSL7692		combination of FSTD(s)	
	Date of birth (yyyy-mm-dd)		State of licence iss	ue	Licence n	10	
C. To be	Last name			First and middle nam	es		
completed by	Last name			i iist and middle nam	<b>C</b> 3		
41	Street or box			Country		Telephone	
the applicant	Postal code and city			E-mail address			
	Total flight time	Total tir	me as PIC/PICUS /	Instrument time/Ground time /		FFS/FNPT /	
	Total time MPO	Cross-c	country PIC/PICUS	Night flight		Intentionally left blank	
			/				
	Applicant verification of c	omplianc	e according to ARA.	GEN.315 and AMC1 AR	RA.GEN.315	5 (c) (See instructions, page 9)	
D. To be	TRAINING COMPLET	ED AN	ID APPLICATI		)		
completed by	Name and number of ATO/AOC			Date			
	Flight time during course			Total time in FS/FFS	during coul	rse	
the ATO				FTD:	FFS:		
	Refresher training completed	Atte	ending ZFTT rse	Approved for PC renewal		course leted	
	Recommendation by Head of Tra nominated by the Head of Training		other person	Name in block letters			
	Result of the test			<u> </u>			
E. To be completed by	If 1-5 iter	ns are f	re passed failed ns are failed	– Final resul – Final resul – Final resul	t : Partial		
the examiner	Final result:				t . Falleu		
		☐ P	Passed	☐ Partial pass		Failed	
			Tempora	ary rating issued			
			red the following of test/check	details in the appli Rating valid u		ence IR valid until	
	Rating	Date	, or leaveneer	Naung vanu t	ariui	in valid diffil	
	Examiner's certificate number:			Stamp/Printed name			
	Signature of examiner:						



Mandatory before each test/check						
☐ Technical training (initial issue only)						
☐ Valid or expired IR/ME (Ini	tial issue only)					
☐ AUPRT (certificate or verification attached, if required, see page 10 section F)						
☐ Valid CPL/MPL/ATPL licence						
☐ Valid language proficiency (req. if test performed in aircraft)						
☐ Valid medical certificate (re	eq. if test performed in aircraft)					
Personal identification card	d					
☐ In case of non-Swedish A	TO, required documentation attac	hed (see page 9 section D)				
☐ In case of non-Swedish ex	aminer, required documentation	attached (see page 9 section E				
In case of non-Swedish examiner, required documentation attached (see page 9 section E   Before PC, revalidation   Valid type rating   Approved training   Approved training   Performed by ATO   Copy of course completion certificate must be attached unless section D, on page 1, is completed by an ATO)   See instructions for PICUS, if applicable, on page 10						
EDD revision nr:						
Examiner						
E-mail of non-Swedish examiner						
L man or non owedien examine						
Before PBN test/check (initial)  ☐ Approved to be tested on P	RN					
	N privileges not confirmed in logbook or by other mea	ans)				
Before test/check if PBN appro	ach is not included in the test					
☐ Applicant has previously me (must be confirmed by logbook entry or ope						
	cluding PBN approach, applicant	informed of limitations in				
in thollowing a successful te	ot.					

M=Mandatory exercise or a choice where more than one exercise appears P=Trained as PIC or COP and as PF and PNF for issue X=FS only (see instructions) or simulated IMC

P# = the training shall be complemented by supervised aeroplane inspection





G.

		FSTD		Instructore initials when	l ested or		
SECTI	ON 1 FLIGHT PREPARATION	5	⋖	Instructors initials when training completed	checked in FSTD or A	Pass	Fail
		OTD					
1.1	Performance calculation	P					
1.2	Aeroplane external visual	OTD				_	
	inspection; location of each item and purpose of inspection	P#	Р				
1.3	Cockpit inspection	P→	$\rightarrow$				
1.4	Use of checklist prior to starting engines, starting procedures, radio and navigation equipment check, selection and setting of navigation and communication frequencies	P→	<b>→</b>		М		
1.5	Taxiing in compliance with air traffic control or instructions of instructor	P→	$\rightarrow$				
1.6	Before take-off checks	P→	$\rightarrow$		М		
	l	1		Examiners initials when			
				test section completed			
				,			
					Tooted as		
		FSTD		Instructors initials when	Tested or checked in		
SECTI	ON 2 TAKE-OFFS	Ű.	٧	training completed	FSTD or A	Pass	Fail
2.1	Normal take offs with different flap settings, including expedited take off	P→	$\rightarrow$				
2.2*	Instrument take-off; transition to instrument flight is required during rotation or immediately after becoming airborne	P→	$\rightarrow$				
2.3	Cross wind take-off (A, if practicable)	P→	$\rightarrow$				
2.4	Take-off at maximum takeoff mass (actual or simulated maximum take-off mass)	P→	$\rightarrow$				
2.5	Take-offs with simulated engine failure:						
2.5.1*	- shortly after reaching V2 (In aeroplanes which are not certificated as transport category aeroplanes (JAR/FAR 25) or as commuter category aeroplanes (SFAR 23), the engine failure shall not be simulated until reaching a minimum height of 500ft above runway end. In aeroplanes having the same performance as a transport category aeroplane regarding take-off mass and density altitude, the instructor may simulate the engine failure shortly after reaching V2.)	P→	<b>→</b>				
2.5.2*	- between V <sub>1</sub> and V <sub>2</sub>	Р	x		<b>M</b> FFS Only		
2.6	Rejected take-off at a reasonable speed before reaching V <sub>1</sub> .	P→	<b>→</b>		М		
			•	Examiners initials when			
				test section completed			



	ON 3 FLIGHT MANEUVRES ROCEDURES	FSTD	∢	Instructors initials when training completed	Tested or checked in FSTD or A	Pass	Fail
3.1	Manual flight with and without flight directors (no autopilot, no auto thrust/auto throttle, and at different control laws, where applicable)	P→	$\rightarrow$				
3.1.1	At different speeds (including slow flight) and altitudes within the FSTD training envelope	P→	<b>→</b>				
3.1.2	Steep turns using 45° bank, 180° to 360° left and right	P→	$\rightarrow$				
3.1.3	Turns with and without Spoilers	P→	$\rightarrow$				
3.1.4	Procedural instrument flying and manoeuvring including instrument departure and arrival, and visual approach	P→	$\rightarrow$				
3.2	Tuck under and Mach buffets after reaching the critical Mach number, and other specific flight characteristics of the aeroplane (e.g. Dutch Roll)	P→	→X An aircraft may not be used for this exercise				
3.3	Normal operation of systems and controls engineer's panel	OTD→	$\rightarrow$				
operat (A man	rmal and abnormal ions of following systems: datory minimum of 3 items shall cted from 3.4.0 to 3.4.14 re)				М		
3.4.0	Engine (if necessary propeller)	$OTD \rightarrow$	$\rightarrow$				
3.4.1	Pressurisation and airconditioning	$OTD \to$	$\rightarrow$				
3.4.2	Pitot/static system	$OTD \rightarrow$	$\rightarrow$				
3.4.3	Fuel system	$OTD \rightarrow$	$\rightarrow$				
3.4.4	Electrical system	$OTD \rightarrow$	$\rightarrow$				
3.4.5	Hydraulic system	$OTD \to$	$\rightarrow$				
3.4.6	Flight control and trim system	$OTD \to$	$\rightarrow$				
3.4.7	Anti- and de-icing system, Glare shield heating	$OTD \to$	$\rightarrow$				
3.4.8	Autopilot/Flight director	$OTD \rightarrow$	$\rightarrow$		M (single pilot only)		
3.4.9	Stall warning devices or stall avoidance devices, and stability augmentation devices	$OTD \rightarrow$	$\rightarrow$				
3.4.10	Ground proximity warning system Weather radar, radio altimeter, transponder	P→	$\rightarrow$				
3.4.11	Radios, navigation equipment, instruments, flight management system	$OTD \rightarrow$	$\rightarrow$				
3.4.12	Landing gear and brake	OTD P →	$\rightarrow$				
3.4.13	Slat and flap system	$OTD \rightarrow$	$\rightarrow$				
3.4.14	Auxiliary power unit	OTD P →	$\rightarrow$				



	normal and emergency				Tested or		
	ures: A mandatory minimum of 3	FSTD			checked		
	nall be selected from 3.6.1 to	S	⋖	Instructors initials when	in FSTD		
3.6.9 in		ш	1	training completed	or A	Pass	Fail
3.6.1	Fire drills e.g. Engine, APU, cabin, cargo compartment, flight	P→	$\rightarrow$				
	deck, wing and electrical fires including evacuation.						
3.6.2	Smoke control and removal	P→	$\rightarrow$				
3.6.3	Engine failures, shut-down	P→	$\rightarrow$				
3.6.4	and restart at a safe height Fuel dumping (simulated)	_				Ш	
	, , ,	P→	$\rightarrow$				
3.6.5	Wind shear at Take off/ Landing	Р	x		FFS only		
3.6.6	Simulated cabin pressure failure/Emergency descent	P→	$\rightarrow$				
3.6.7	Incapacitation of flight crew Member	P→	$\rightarrow$				
3.6.8	Other emergency procedures as						
	outlined in the appropriate aeroplane Flight Manual	$\rightarrow$	$\rightarrow$				Ш
3.6.9	TCAS event	OTD	x				
		P→	^		FFS only		
3.7	Upset recovery training						
3.7.1	Recovery from stall events in:	P FFS	X An aero-				
	<ul><li>take-off configuration;</li><li>clean configuration at low</li></ul>	qualified for the	plane				
	altitude;	training	shall not be used				
	<ul> <li>clean configuration near maximum operating altitude; and – landing configuration.</li> </ul>	task only	for this exercise				
3.7.2	The following upset exercises:	Р	Х				
	<ul> <li>recovery from nose-high at</li> </ul>	FFS	An aero-				
	various bank angles; and	qualified	plane shall not be				
	<ul> <li>recovery from nose-low at</li> </ul>	for the	used for			Ш	
	various bank angles	training task only	this exercise				
3.8 Inst	rument flight procedures						
3.8.1	Adherence to departure and		-				
0.0.1	arrival routes and ATC instructions	P→	$\rightarrow$		М		
3.8.2	Holding procedures	P→	$\rightarrow$				
3.8.3*	3D operations to DH/A of 200 feet (60 m) or to higher minima of required by approach procedure						
	required by approach procedure						
	ly shall be chosen taking into acc			require the use of autopilot or flight directions (for example, choose an ILS for 3.8.			
3.8.3.1*	- manually, without flight	P→					
	director	P→	$\rightarrow$		<b>M</b> (skill test only)		
3.8.3.2*	- manually, with flight director	P→	$\rightarrow$				
3.8.3.3*	- with autopilot	P→	$\rightarrow$				





3.8.3.4*	Manually, with one engine simulated inoperative during final approach,						
	either until touchdown or through the complete missed approach						
	procedure (as applicable), starting:						
	(i) before passing 1 000 ft						
	above aerodrome level; and						
	(ii) after passing 1 000 ft						
	above aerodrome level.						
	In aeroplanes which are not certificated as transport category aeroplanes (JAR/FAR 25) or as commuter category aeroplanes (SFAR 23), the approach with simulated engine failure and the ensuing go- around shall be initiated in conjunction with the 2D approach in accordance with 3.8.4. The go- around shall be initiated when reaching the published obstacle clearance height/altitude (OCH/A); however, not later than reaching an MDH/A of 500 ft above the runway threshold elevation. In aeroplanes having the same performance as a transport category aeroplane regarding takeoff mass and density altitude, the instructor may simulate the engine failure in accordance with exercise 3.8.3.4.	P→	<b>→</b>		M choice of (i) or (ii) or both		
3.8.4*	2D operations down to the MDH/A	P*→	<b>→</b>		М		
To estab	<u>l</u> llish or maintain PBN privileges, one a	l pproach sl	nall be an	L RNP APCH. Where an RNP APCH is not pra	L cticable, it sh	l all be perforr	ned in an
appropri	ately equipped FSTD.						
APCH e				e a proficiency check for revalidation of PBN p P APCH. The restriction shall be lifted if the p			
3.8.5*	Circling approach under following conditions:  (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a), at the authorised minimum circling approach altitude; Remark: if a) and b) are not possible due to ATC reasons a simulated low visibility pattern may be performed	P*→	<b>→</b>				
3.8.6*	Visual approaches	P→	$\rightarrow$				
	l	1	1	Examiners initials when	<u> </u>		
				test section completed			





-	ION 4 MISSED APPROACH	FSTD	⋖	Instructors initials when training completed	Tested or checked in FSTD or A	Pass	Fail
4.1*	Go-around with all engines operating* during a 3D operation on reaching decision height	P*→	$\rightarrow$				
4.2	Go-around with all engines operating* from various stages during an instrument approach	P*→	$\rightarrow$				
4.3	Other missed approach Procedures	P*→	$\rightarrow$				
4.4*	Manual Go-around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt	P*→	$\rightarrow$		М		
4.5	Rejected landing with all engines operating:  – from various heights below DH/MDH;  – after touchdown (baulked landing) In aeroplanes which are not certificated as transport category aeroplanes (JAR/FAR 25) or as commuter category aeroplanes (SFAR 23), the rejected landing with all engines operating shall be initiated below MDH/A or after touchdown.	P→	$\rightarrow$				
				Examiners initials when			
				test section completed			
SECT	TION 5 LANDINGS	FSTD	<	Instructors initials when training completed	Tested or checked in FSTD or A	Pass	Fail
5.1	Normal landings* with visual reference established when reaching DA/H following an instrument approach operation	Р		taning completed	1 0 1 5 01 7 1		
5.2	Landing with simulated jammed horizontal stabiliser in any out-of-trim position.	P→	An aircraft may not be used for this exercise		FFS only		
5.3	Cross wind landings (a/c, if practicable).	P→	$\rightarrow$				
5.4	Traffic pattern and landing without extended or with partly extended flaps and slats.	P→	<b>→</b>				
5.5	Landing with critical engine simulated inoperative.	P→	$\rightarrow$		М		
5.6	Landing with two engines inoperative  - Aeroplanes with three engines: the centre engine and one outboard engine as far as practicable according to data	Р	х		M FFS only (skill test only)		
	of the AFM.  - Aeroplanes with four engines, two engines at one side.						

test section completed.....





Details of the flight					
Registration of A/C and/or	FSTD qualification no	Block on	On ground		
Departure aerodrome		Block off	Take-off		
Destination aerodrome		Total block	Total		
Aeroplane variant		Applicant tested as	PIC		
		PF PNF			
DEMARKS					
REMARKS	Comment				
Item no	Comment				
Signature of applicant if required					
Signature of applicant if red	quired				
Signature of applicant if red	quired				
Signature of applicant if rec	quired				
Signature of applicant if red	quired				
Signature of applicant if red					

To document ZFTT and Aircraft training, use TSL7783



ATPL(A), Type rating multi pilot aeroplane and single pilot complex aeroplanes with high performance, Proficiency check multi pilot aeroplane and single pilot complex aeroplane with high performance,

#### Instructions for completing form

- A. Please tick the appropriate boxes for relevant test/check. Please note the following;
  - PC Renewal: If the rating has lapsed the applicant must have, at an ATO, been evaluated whether refresher
    training is necessary for the applicant to reach the level of proficiency to safely operate the aircraft accordance
    with FCL.740. Either section D has to be completed or a course completion certificate has to be attached to the
    application as indicated in section F, with the relevant information regarding the assessment regardless if any
    training was found necessary.
  - If the test is performed in a single pilot airplane in either single or multi pilot operations, tick the appropriate box. If privileges for both single-pilot and multi-pilot privileges are sought, complete the additional exercises, tick both boxes and complete form TSL7692 (instructions are available on the form)
- **B.** Please enter the complete information. "Licence endorsement" means the relevant type of aeroplane according to EASA Class and Type Rating List (Aeroplanes).
- **C.** Personal information of the applicant, always required

The following shall be documented before a Proficiency check;

• Total flight time

The following shall be checked in the applicant's pilot logbook (conventional or electronic) and documented before a type skilltest

• At least 70 hours PIC (Unless undergoing an MPL training course)

The following shall be checked in the applicant's pilot logbook (conventional or electronic) and documented before an ATPL skilltest

- At least 1500 hours of flight time in aeroplanes
- 500 hours in multi-pilot operations on aeroplanes
- 500 hours as PIC under supervision; or
  - o 250 hours as PIC; or
  - 250 hours, including at least 70 hours as PIC, and the remaining as PIC under supervision.
- 200 hours of cross-country flight time of which at least 100 hours shall be as PIC or as PIC under supervision
- 75 hours of instrument time of which not more than 30 hours may be instrument ground time
- 100 hours of night flight as PIC or co-pilot
- Out of the 1500 hours of flight time, up to 100 hours of flight time may have been completed in an FFS and FNPT. Of these 100 hours, only a maximum of 25 hours may be completed in an FNPT.

#### AMC1 ARA.GEN.315 Applicant VERIFICATION OF COMPLIANCE By ticking this box you certify that you:

- (1) do not hold any personnel licence, certificate, rating, authorisation or attestation with the same scope and in the same category issued in another Member State;
- (2) has not applied for any personnel licence, certificate, rating, authorisation or attestation with the same scope and in the same category in another Member State; and
- (3) has never held any personnel licence, certificate, rating, authorisation or attestation with the same scope and in the same category issued in another Member State which was revoked or suspended in any other Member State. Incorrect information could disqualify you from being granted a personnel licence, certificate, rating, authorization or attestation.
- D. This section is to be completed by the Head of Training of the ATO if the purpose is a skill test after basic training or a PC after approved refresher training for the renewal of a lapsed type- or class rating. If the training is performed as an approved zero flight time training course, the head of training must indicate it in the appropriate box.

Applicants who have completed a Part-FCL type rating course at a non-Swedish ATO must attach the following documents to the application:

- Course completion certificate or section D completed.
- ATO Approval Certificate.
- FSTD qualification certificate.
- The Examiners certificate documents including copy of the licence.
- Copy of the licence of the TRI responsible for the aircraft training or LIFUS as applicable.

To remove the CRCP restriction, applicants shall comply with all of the following: (1) undergo an assessment at an ATO which shall determine their training needs to have the restriction removed; (2) based on the assessment specified in point (1), complete, at that ATO, training which shall allow them to reach the level of proficiency to safely operate the aircraft; (3) after the completion of the training specified in point (2), complete a skill test in accordance with Appendix 9; (4) after the completion of the skill test specified in point (3), meet one of the following conditions: (i) comply with point ORO.FC.220(e) of Annex III (Part-ORO) to Regulation (EU) No 965/2012, provided that they meet the experience requirements specified in point FCL.730.A of this Annex; (ii) complete flight training in the aircraft which includes manoeuvres on take-off, landing and go-around.

E. The result of the test. In case of non-Swedish examiner, the following attachments are required;
The Examiners license with rating and instructor certificate clearly visible and examiner certificate containing the scope of his/her privileges as examiner.



F. This section is a checklist with prerequisites for the examiner to check before the test/check. Please mind that a

AUPRT is required according to the table below and a certificate or verification of training/checking must be attached to the application.

First typerating AUPRT required

MPA→MPA AUPRT not required (credited)
SPA→SPA AUPRT not required (credited)

SPA→MPA AUPRT required\*
MPA→SPA AUPRT required\*

- \* An Advanced UPRT course is not required for a pilot who, within the three preceding years, has completed one of the following;
  - all the training and checking items in accordance with points ORO.FC.220 and ORO.FC.230 of Annex III (Part-ORO) to Regulation (EU) No 965/2012 or;
  - completed the training for an AUPRT instructor specified in point FCL.915(e)(1)(ii).

Applicants who wish to convert a third-country type rating into a Part-FCL type rating need to comply with the advanced UPRT prerequisite

If the applicant states PICUS flight experience, verification is required according to the following: Crediting of Pilot In Command Under Supervision (PICUS) flight time, with the purpose of reaching the requirement for an ATPL skilltest may be recorded as long as it is performed in accordance with AMC1 FCL.050 (b) (5). The Swedish transport agency require a written verification, from a manager such as a chief pilot, NP flight operations, chief flight instructor or equivalent position in the organization that the recording of the PICUS time has been done in accordance with AMC1 FCL.050 (b) (5). The actual recording of the PICUS flight time shall be done in accordance with AMC 1 FCL.050 (b) (1) (v).

#### Please note that the examiner must sign and thus affirm that he has checked all prerequisites before the test.

- **G**. 1. The following symbols mean:
  - P = Trained as Pilot-in-command or Co-pilot and as Pilot Flying (PF) and Pilot Not Flying (PNF) for the issue of a type rating as applicable.
  - X = Simulators shall be used for this exercise, if available, otherwise an aircraft shall be used if appropriate for the manoeuvre or procedure.
  - P# = the training shall be complemented by supervised aeroplane inspection
  - The practical training shall be conducted at least at the training equipment level shown as (P), but may be conducted up to any higher equipment level shown by the arrow (→).

The following abbreviations are used to indicate the training equipment used:

A = Aeroplane

FFS = Flight Simulator

OTD = Other Training Devices

- 3. The starred items (\*) shall be flown solely by reference to instruments. If this condition is not met during the skill test or proficiency check, the type rating will be restricted to VFR only.
- 4. Where the letter 'M' appears in the skill test/proficiency check column this indicates a mandatory exercise.
- 5. A flight simulator shall be used for practical training and testing if the simulator forms part of an approved typerating course. The following considerations will apply to the approval of the course:
  - a. the qualification of the flight simulator or FNPTII as set out in Part-ORA:
  - b. the qualifications of the instructor and examiner;
  - c. the amount of line-orientated simulator training provided on the course;
  - d. the qualifications and previous line operating experience of the pilot under training; and
  - e. the amount of supervised line flying experience provided after the issue of the new type rating.
- 6. In the case of single-pilot high performance complex aeroplanes, when a skill test or proficiency check is performed in multi-pilot operations, the type rating shall be restricted to multi-pilot operations. If privileges of single-pilot are sought, the manoeuvres/procedures in 2.5, 3.9.3.4, 4.3, 5.5 and at least one manoeuvre/procedure from section 3.4 have to be completed in addition as single-pilot.



7. The following limits shall apply corrected to make allowance for turbulent conditions and the handling qualities and performance of the aeroplane used:

#### Height:

Generally	±100 feet
Starting a go-around at decision height	+50 feet/-0 feet
Minimum descent height/altitude	+50 feet/-0 feet

Tracking:

racking.	
On radio aids	±5°
For "angular" deviations	Half scale deflection, azimuth and glide path (e.g. LPV, ILS, MLS, GLS)
2D (LNAV) and 3D (LNAV/VNAV) "linear" deviations	Cross track error/deviation shall normally be limited to ± ½ the RNP value associated with the procedure. Brief deviations from this standard up to a maximum of 1 time the RNP value are allowed.
3D linear vertical deviations (e.g. RNP APCH (LNAV/VNAV) using BaroVNAV)	Not more than -75 feet below the vertical profile at any time, and not more than +75 feet above the vertical profile at or below 1000 feet above aerodrome level.

#### Heading:

All engines operating	±5°
With simulated engine failure	±10°

Speed:

Ĺ	All engines operating	±5 knots
	With simulated engine failure	+10 knots/-5 knots

- 8. To establish or maintain PBN privileges one approach shall be an RNP APCH. Where an RNP APCH is not practicable, it shall be performed in an appropriately equipped FSTD.
- **H.** Details of the flight .Please enter the simulator approval number if the test is conducted in a simulator.
- I. Comments regarding the conduct of items.
- J. Additional information regarding the conditions during the test/check. E.g. Staff, weather etc.